



EC-3

EC-400

ECCM-450

EC-520

ECC-520

mod.	rango range °C	largo length (mm)	alto height (mm)	fondo depth (mm)	estantes shelves	capacidad capacity (L)	voltaje voltage	refrigerante refrigerant	potencia frig. frig. power W	potencia power W
EC-3	0°C +7°C	410	512	452	1	30	230V-50Hz	R600a	115	72
EC-400	0°C +7°C	450	740	500	2	52	230V-50Hz	R600a	144	84
ECCM-450	0°C +7°C	450	900	500	2	72	230V-50Hz	R600a	144	87
ECC-520	0°C +7°C	520	1100	570	2	115	230V-50Hz	R600a	144	117
EC-520	0°C +7°C	520	945	560	2	115	230V-50Hz	R600a	144	114

Características técnicas y constructivas sujetas a variación sin previo aviso.

We reserve the right to change specifications without prior notice.

EC-3 / EC-400 / ECCM-450

- Exterior e interior en acero plastificado blanco

ECC / EC-520

 - Exterior en acero plastificado blanco
 - Interior en poliestireno sanitario termo-conformado

EC-3 / EC-400 / ECCM-450

- Exterior and interior in white plastic coated steel

ECC / EC-520

 - White plastic coated steel exterior
 - Interior in sanitary polystyrene thermoforming

CARACTERISTICAS COMUNES

- Diseñados para bebidas y productos envasados
- Puerta con doble cristal sobre marco de aluminio
- Estantes de alambre de acero plastificado, regulables en altura
- Compresor hermético alto par de arranque
- Evaporador ventilado impreso en placa de aluminio
- Control digital de temperatura y descarches
- Iluminación interior LEDs
- Unidad condensadora ventilada
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- Evaporación automática del agua de descarche
- Temperatura de trabajo 32°C ambiente
- Tensión monofásica 230V - 50 Hz

FEATURES IN COMMON

- Designed for beverages and packaged
- Double glass doors with aluminium frame
- Shelves plastic coated steel wire, adjustable height
- Hermetic compressor higher starting torque
- Ventilated evaporator printed on aluminum plate
- Digital temperature control and defrost
- Interior LEDs lighting
- Ventilated condensing unit
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Automatic evaporation of defrost water
- Operating temperature 32°C ambient
- Voltage 230V - 50 Hz

